



ROMI

CNC TEACH LATHES

ROMI C 1000BB

Front and rear chuck up to
Ø14.8" through-bore

Easy to learn CNC w/ conversational programming
No G-code experience necessary



Traveling chip guard

Heavy-duty machine structure
made of high quality cast iron



ROMI C 420

ROMI C 510

ROMI C 620

ROMI C 680

ROMI C 830

ROMI C 1000

ROMI C 1000BB

Standard Features

- 45-Horsepower AC main motor
- 2-Speed Gearbox
- Front and Rear chuck
- Ø 14.8" through-bore
- Advanced intuitive programming system
- Thread repair cycles
- USB, Ethernet and Compact Flash ports
- CE Fully enclosed splash guard
- 3 Mb Program memory

Plus...

- 2-electronic hand wheels with Teach-in mode
- Tailstock with adjustable quill
- Remote Jog Handle
- Spindle orientation
- Coolant pump kit
- Rigid tapping
- User-created macros
- 200-480VCA power supply
- 24 months control warranty (parts and labor).

Options | partial list

- Manual chucks
- 4-station and 8-Station automatic turrets
- Tool post / tool holders
- Hydraulic tailstock quill
- Steady rests
- Upgrade to chip conveyor hinged belt
- Robot interface
- Remote diagnosis



ROMI Machine Tools, Ltd. | www.romiusa.com | (859) 647-7566

Specifications subject to change without notice



CNC Lathes from ROMI C Series are machines with great versatility for machining different types of parts, with great levels of power, quick movements and machining accuracy.

The robust structure provides the rigidity and stability needed to achieve the best performance over a wide variety of machining conditions.

State of the Art Performance and Reliability

The ultimate in accuracy - control equipped with 80-bit NANOPF accuracy.

Guideways - hardened and ground to ensure high wear resistance. Its self adjusting system assures permanent contact between the cross slide and the machine bed.

Movable Apron - offers the operator the convenience preferred during Manual machining or during setup.



Capacities	INCH	METRIC
Center Heights	20.1 in	510 mm
Distance Between Centers	120 in	3,000 mm
Swing Over Bed	39.4 in	1,000 mm
Swing Over Cross Slide	27.6 in	700 mm
Slide Travel In / Out (X-Axis)	20.5 in	520 mm
Linear Carriage Travel (Z-Axis)	118.9 in	3,020 mm

Bed	INCH	METRIC
Width	18.1 in	460 mm
Height	16.5 in	420 mm

Headstock	INCH	METRIC
Spindle Nose	A2-20"	A2-20"
Spindle Bore	14.76 in	375 mm
Recommended Chuck Size Up To	31.50 in	800 mm
Speed Ranges	400 rpm	400 rpm
ID Spindle Bearing	17.00 in	431.8 mm

Feeds	INCH	METRIC
Rapid Traverse (Z-Axis) - 120" bed	315 ipm	8 m/min
Rapid Traverse (X-Axis)	315 ipm	8 m/min

Manual Tailstock	INCH	METRIC
Tailstock Positioning	Drag by the table	
Quill Drive	Manual or Opt. Hydraulic	
Maximum Quill Stroke	7.87 in	200 mm
Quill Diameter	5.12 in	130 mm
Quill Taper Hole	5 MT	5 MT

Installed Power	INCH	METRIC
AC Main Motor	45.0 HP	33.6 kW

Power Supply	INCH	METRIC
	200 to 480V, 3Phase, 40kVA	

Floor Space	INCH	METRIC
	296 x 126 in	7.52 x 3.20 m

Weight	INCH	METRIC
	25,520 lbs	11,600 kg